

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 February 2005 (17.02.2005)

PCT

(10) International Publication Number
WO 2005/015035 A1

(51) International Patent Classification⁷: F16C 33/10

(21) International Application Number:
PCT/EP2004/009096

(22) International Filing Date: 12 August 2004 (12.08.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
1024091 12 August 2003 (12.08.2003) NL

(71) Applicant (for all designated States except US): AB SKF
[SE/SE]; Hornsgatan 1, S-415 50 Göteborg (SE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): IOANNIDES,
Eusthassios [GR/NL]; Montessorilaan 9, NL-3706 TB
Zeist (NL). SPIKES, Hugh, Alexander [GB/GB]; Flat 3,
Lexham Gardens, London W8 5JJ (GB). BRAJIC-MITI-
DIERI, Petra [HR/GB]; 56D Caversham Road, London,
NW 2DR (GB). GOSMAN, Allen, David [GB/GB]; 15
Home Park Road, London, SW 19 (GB).

(74) Agent: VAN WESTENBRUGGE, Andries; Nederland-
sch Octrooibureau, Scheveningsweg 82, P.O. Box 29720,
NL-2502 LS The Hague (NL).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PI, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARTPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: SLIDING BEARING WITH IMPROVED SURFACE TOPOGRAPHY



(57) Abstract: A sliding bearing comprises two opposite bearing surfaces (3, 4) which enclose a gap (6) containing a lubricant film (5), said bearing surfaces (3, 4) being moveable with respect to each other in a generally parallel fashion, at least one of said surfaces (4) being provided with at least one cavity (10), said cavity having a depth (h3) which is at least equal to the lubricant film thickness. One of the length (Bp) and width (Lp) dimension of the surface area of said cavity (10) amounts to at least 100 µm.

WO 2005/015035 A1

BEST AVAILABLE COPY